

**Proceedings of the  
2015 International Conference on Technology,  
Information, Management, Engineering and  
Environment**

**Samosir Island, North Sumatra, Indonesia  
September 7-9, 2015**



**IEEE Catalog Number: CFP1564U-ART  
ISBN: 978-1-4673-7411-8**

**Organized by:**



**IEEE Indonesia Control System (SC) /  
Robotics & Automation (RA) Joint Societies Chapter**

**Supported by:**



# Conference Organization

## **General Chair**

Endra Joelianto (Institute of Technology Bandung, Indonesia)

## **General Co-Chair**

Arjon Turnip (Indonesian Institute of Science, Indonesia)

## **Secretariat**

Miranti Indah Mandasari (Institute of Technology Bandung, Indonesia)

## **Treasury Chair**

Muhammad Ary Murti (Telkom University, Indonesia)

## **Technical Program Chair**

Augie Widyotriatmo (Institute of Technology Bandung, Indonesia)

## **Conference Editorial Board Chair**

Tua Agustinus Tamba (Institute of Technology Bandung, Indonesia)

## **Publication Chair**

Maclaurin Hutagalung (Institute of Technology Harapan Bangsa, Indonesia)

## **Local Arrangement**

Tumiur Gultom (State University of Medan, Indonesia)

Mariati Simanjuntak (State University of Medan, Indonesia)

Janner Simamarta (State University of Medan, Indonesia)

Marzuki Sinambela (BMKG, Indonesia)

Mardi Turnip (Prima University, Indonesia)

# Conference Organization

## International Program Committee

Zakarias Situmorang (*Saint Thomas Catholic University, Indonesia*)  
Himsar Ambarita (*North Sumatra University, Indonesia*)  
Godlif Sianipar (*Saint Thomas Catholic University, Indonesia*)  
Anna Antonyová (*University of Prešov, Slovakia*)  
Toni Anwar (*Universiti Teknologi Malaysia, Malaysia*)  
Vo Nguyen Quoc Bao (*Posts & Telecomm. Institute of Technology, Vietnam*)  
Alfred So Ping Lam (*Nanyang Technological University, Singapore*)  
Teddy Mantoro (*Universiti Teknologi Malaysia, Malaysia*)  
Albinur Limbong (*Universitas Advent Indonesia, Indonesia*)  
Habibah Hashim (*Universitas Teknologi Mara, Malaysia*)  
Mahamod Bin Ismail (*Universiti Kebangsaan Malaysia, Malaysia*)  
Eunmi Choi (*Kookmin University, Korea*)  
Agus Budiyo (*Konkuk University, Korea*)  
Dugki Min (*Konkuk University, Korea*)  
Hew Wooi Ping (*University of Malaysia, Malaysia*)  
Animesh Dutta (*Asian Institute of Technology, Thailand*)  
Rafiuddin Syam (*Hasanuddin University, Indonesia*)  
Hoang Minh Son (*Hanoi University of Technology, Vietnam*)  
Vadakkepat Prahlad (*National University of Singapore, Singapore*)  
Supavadee Aramvith (*Chulalongkorn University, Thailand*)  
Keum-Shik Hong (*Pusan National University, Korea*)  
Jenny Dankelman (*Delft University of Technology, Netherlands*)  
Danwei Wang (*Nanyang Technological University, Singapore*)  
Udisubakti Ciptomulyono (*Institut Teknologi Sepuluh November, Indonesia*)  
Bermawi Iskandar (*Institute of Technology Bandung, Indonesia*)  
Soo-Hong Lee (*Yonsei University, Korea*)  
Gordana Jovanovic Dolecek (*National Institute INAOE, Mexico*)  
P. Sanjeevikumar (*Dublin Institute of Technology, Ireland*)

## TABLE OF CONTENT

	Page
<b>Copyright .....</b>	ii
<b>Welcome Message .....</b>	iii
<b>Conference Organization .....</b>	iv
<b>List of Technical Committee Members and Reviewers .....</b>	vi
<b>Technical Sessions .....</b>	viii
<b>1 Protocol for E-Commerce Data Harvesting</b>	
<i>Dani Gunawan (University of Sumatera Utara) .....</i>	1
<b>2 Supporting Collaborative Emergency Response System with Reputation-based Trust Peer-to-Peer File Sharing</b>	
<i>Vitri Tundjungsari (YARSI University), Heri Yugaswara (YARSI University).....</i>	6
<b>3 Study on Quantitative Measurement of Chromatin Size of Cervical Cell Images</b>	
<i>Jing Rui Tang (Universiti Sains Malaysia), Nor Ashidi Mat Isa (Universiti Sains Malaysia), Ewe Seng Ch'ng (Universiti Sains Malaysia) .....</i>	12
<b>4 Optimal Number of Fishing Fleet for a Sustainable Fishery Industry</b>	
<i>H. Husniah (Langlangbuana University), A. K. Supriatna (Padjadjaran University).....</i>	18
<b>5 Modelling and Analysis of Maintenance Contract with Imperfect Preventive Maintenance</b>	
<i>H. Husniah (Langlangbuana University), A. Cakravastia (Institut Teknologi Bandung), U. S. Pasaribu (Institut Teknologi Bandung), B. P. Iskandar (Institut Teknologi Bandung).....</i>	25
<b>6 The Influence of Website Quality, Brand Awareness and Perceived Product Quality on Purchase Intention of Video Games Online Store</b>	
<i>Idris Gautama So (Bina Nusantara University), Bachtiar Simamora (Bina Nusantara University), Natalia (Bina Nusantara University), Steven (Bina Nusantara University) .....</i>	31
<b>7 Segmentation of Online Buyers and Its Implication in Determining Marketing Strategies (Indonesian Case Study)</b>	
<i>Hasrini Sari (Institut Teknologi Bandung), A. P. Setiaboedi (Institut Teknologi Bandung).....</i>	34
<b>8 Inventory Model for Deteriorating Items with Expired Time in Lost-Sales Probabilistic Demand (Pharmacy Case Study)</b>	

	<i>Yosi Agustina Hidayat (Institut Teknologi Bandung), Muhammad Ridhwan Fauzi (Institut Teknologi Bandung) .....</i>	40
9	<b>Methodology with Analytical Approach to Testing the Conditions for Growing the Cultivators in the Experimental Laboratory</b> <i>Anna Antonyová (University of Presov), Peter Antony (Apmikro), Endra Joelianto (Institut Teknologi Bandung) .....</i>	47
10	<b>A Heuristic Hidden Markov Model to Recognize Inflectional Words in Sign System for Indonesian Language known as SIBI (Sistem Isyarat Bahasa Indonesia)</b> <i>Erdefi Rakun (Universitas Indonesia), Mohammad Ivan Fanany (Universitas Indonesia), I Wayan Wiprayoga Wisesa (Universitas Indonesia), Andros Tjandra (Universitas Indonesia).....</i>	53
11	<b>Induction, Multiplication, and Acclimatization of Rodent Tuber (Typhonium flagelliforme Lodd.) Plant From Indonesia by In Vitro Organogenesis</b> <i>Nesti Fronika Sianipar (Bina Nusantara University), Danny Laurent (University of Edinburgh), Chelen (Pelita Harapan University), Rosaria (Pelita Harapan University) .....</i>	59
12	<b>The Role of Knowledge Management in Facilitating Innovation for Sustainable SMEs Performance</b> <i>Ramita Abdul Rahim (Universiti Teknologi Malaysia), Nik Hasnaa Nik Mahmood (Universiti Teknologi Malaysia), Maslin Masrom (Universiti Teknologi Malaysia) .....</i>	64
13	<b>Expert Search Engine and Content Generation in E-Learning System</b> <i>Ravinder Bahl (University of Jammu), Chandra Mauli Sharma (Delhi University), Suruchi Gautam (Uttarakhand Technical University and Technology).....</i>	71
14	<b>Phase Space of Self-Motion and Mechanism Path Tracking</b> <i>A. Machmudah (Universiti Teknologi PETRONAS), S. Parman (Universiti Teknologi PETRONAS), M. B Baharom (Universiti Teknologi PETRONAS).....</i>	76
15	<b>Pedagogy Paradigm: Competency in E-commerce Training for Entrepreneurs</b> <i>Noornasirah Nasri (University Sains Malaysia), Yulita Hanum P Iskandar (University Sains Malaysia).....</i>	82
16	<b>Implementation of A Mamdani Fuzzy Logic Controller for Building Automation Using Electronic Control Based on AT89S51</b> <i>Pilipus Tarigan (STMIK Budidarma Medan), Sinar Sinurat (STMIK Budidarma</i>	

	<i>Medan), Marzuki Sinambela (Indonesia Meteorological Climatological &amp; Geophysical Agency) .....</i>	87
17	<b>Location-based Request Forwarding in A Geo-fencing Application with Multiple Providers</b> <i>Teduh Dirgahayu (Universitas Islam Indonesia), Feri Wijayanto (Universitas Islam Indonesia) .....</i>	93
18	<b>The Effect of Problem Based Learning Model Towards Physics Learning Outcomes At Dynamic Electricity in Class X SMAN 2 Balige</b> <i>Theresa Margaretta Sirait (State University of Medan), Derlina (State University of Medan) .....</i>	99
19	<b>Examining Internet Addiction as a Mediating Role Towards Online Training Utilization and Employee Performance From Task and Social Technology Fit Perspectives</b> <i>Siti Salina Saidin (Universiti Sains Malaysia), Noornina Dahlan (Universiti Malaysia Pahang).....</i>	105
20	<b>Digital Signature for Contract Signing in Service Commerce</b> <i>Emir Husni (Institut Teknologi Bandung), Bramanto Leksono (Institut Teknologi Bandung), Muhammad Ridho Rosa (Institut Teknologi Bandung).....</i>	111
21	<b>Mobile Device Interfaces Illiterate</b> <i>Muhammad Irwan Padli Nasution (Universitas Islam Negeri Sumatera Utara), Septiana Dewi Andriana (STT Harapan), Popi Diana Syafitri (STT Harapan), Eka Rahayu (STT Harapan), Muhammad Ridwan Lubis (STT Harapan).....</i>	117
22	<b>Study of PV Powered Air Conditioning for a Classroom of University of Surabaya</b> <i>Elieser Tarigan (Univ. of Surabaya), Djuwari (Univ. of Surabaya), Fitri Dwi Kartikasari (Univ. of Surabaya), Marc Fleicher (Dalarna University), Brian Howley (Dalarna University).....</i>	121
23	<b>Model Predictive Control of Combined Renewable Energy Sources</b> <i>Ahmad Rofiq (Institut Teknologi Bandung), Augie Widyotriatmo (Institut Teknologi Bandung), Estiyanti Ekawati (Institut Teknologi Bandung).....</i>	127
24	<b>Prediction of Hydrate Formation Conditions in Subsea Pipeline with Genetic Algorithm</b> <i>Aijaz Abbasi (Universiti Teknologi PETRONAS), Fakhrudin Mohd Hashim (Universiti Teknologi PETRONAS) .....</i>	133

<b>25 Automatic Terminal Information System for El Alto Airport</b>	
<i>N. I. Vargas-Cuentas (Escuela Militar de Ingenieria), A. Roman-Gonzalez</i> <i>(Universidad de Ciencias Humanidades)</i> .....	137
<b>26 Utilization of EEG-SSVEP method and ANFIS Classifier for Controlling Electronic Wheelchair</b>	
<i>A. Turnip (Indonesian Institute of Sciences), A. I. Simbolon (Indonesian Institute of Sciences), M. Faizal Amri (Indonesian Institute of Sciences), M. A. Suhendra</i> <i>(Islamic University of Bandung)</i> .....	143
<b>27 Controller Design for Active Suspension System based on Skyhook Reference Model</b>	
<i>A. Turnip (Indonesian Institute of Sciences), I. R. Setiawan (Indonesian Institute of Sciences), M. F. Amri (Indonesian Institute of Sciences), T. A. Tamba (Bandung Institute of Technology)</i> .....	147
<b>28 Intelligent Fuzzy Controller for a Solar Energy Wood Dry Kiln Process</b>	
<i>Z. Situmorang (St. Thomas Catholic University), J.A Situmorang (St. Thomas Catholic University)</i> .....	152



# Study of PV Powered Air Conditioning for a Classroom of University of Surabaya

Elieser Tarigan <sup>\*,#1</sup>, Djuwari <sup>\*2</sup>, Fitri Dwi Kartikasari <sup>#,\*\*3</sup>, Marc Fleicher <sup>###4</sup>, Brian Howley <sup>###5</sup>

<sup>\*</sup>Electrical Engineering, University of Surabaya, Jl. Raya Kalirungkut, Surabaya 60292, Indonesia

<sup>\*\*</sup>Informatics Engineering, University of Surabaya Jl. Raya Kalirungkut, Surabaya 60292, Indonesia

<sup>#</sup>Center for Renewable Energy Studies, PSET, University of Surabaya, Surabaya 6029, Indonesia

<sup>1</sup>elieser@staff.ubaya.ac.id

<sup>2</sup>djuwari@staff.ubaya.ac.id

<sup>3</sup>fitri\_dk@staff.ubaya.ac.id

<sup>###</sup>European Solar Energy School, Dalarna University, Borlange 78100, Sweden

<sup>4</sup>holzfaeller.marc@googlemail.com

<sup>5</sup>brianthowley@gmail.com

**Abstract**— This paper discusses the interaction between PV and air conditioning and how this can be exploited for a classroom at University of Surabaya campus. A cost analysis of the proposed grid-connected systems are calculated, including total investment, payback period and levelized costs. The most efficient way to connect PVs and air conditioning for a classroom is through a grid connected system. Simulation result shows that a 12 kWp PV system and the new AC units of COP 4,0 gives the LCOE about -3,334 IDR/kWh.

**Keywords**—photovoltaic; air conditioning; solar energy; classroom

## I. INTRODUCTION

Renewable energy such as solar can reduce the need to burn fossil fuels and in turn reduce the amount of greenhouse gasses being released into the atmosphere. To promote the use of solar energy, new innovative solutions must be created in both engineering and policy. Air conditioners are becoming more common and are a major strain on energy demands especially in tropical climate countries like Indonesia where air conditioning is used all year round. Up to 50% of buildings energy can be from air conditioning in subtropical regions [1].

There are few publications that have looked into the interaction between air conditioners and photovoltaic electricity. Most research conducted had been in other areas such as solar cooling, like absorption and adsorption. Reference [2] reported a work focused on the design and construction of a direct current (DC) air conditioning system integrated with photovoltaic (PV) system. No DC system was constructed but it contained a breakdown of all vital components for both the air conditioner and PV system. Reference [3] uses a different type of cooling technology but provided a detailed insight into the methodology of designing and sizing a solar cooling system. Not all of the steps proposed can be repeated as the design is for a solar absorption cooling system, however it is a good guideline to follow when planning our design process. Reference [4] studied the possibility of using photovoltaic panels to produce electricity that is used to power the compressor of an inverter

air conditioning unit, without the use of batteries or any inverter regulators.

The peak times for using air conditioning for classroom activity is during the day when the temperature is the highest. PV's peak times are also during the day when the sun is at its strongest. This paper studied the interaction between PV and air conditioning and how this can be exploited for a classroom at University of Surabaya campus. Surabaya is located at the coast on the east side of Java very close to the equator. Surabaya represents a tropical climate, that means the presented system solutions can be adopted to other cities and countries with similar weather.

## II. RESEARCH METHOD

Classroom TF 2.2 (apart of Building TF) of faculty of Engineering University of Surabaya was used and simulated in this study. The capacity of the classroom is 100 seats for students. Inside there are three air conditioners, which are operate during class. In the classroom there are three split type Toshiba RAS-18UAX2 air conditioners. Each air conditioner has a running power of 1.87 kW and a cooling capacity of 5.2 kW. The air conditioners currently installed in the classroom are kind of old and have a poor COP of 2.78.

A user behaviour profile gave a detailed view on the internal and external gains of the classroom. The internal gains come from people, electronics, etc. The room's timetable and number of students taking each class were used to get the number of people using the room. The classroom commonly occupied during 07.00 – 18.30, with a half an hour interval for lunch break during 12.30- 13.30.

Indonesians thumb rule of sizing air conditioners was used by former installer company with 0.5 pk electrical power (paardenkracht Dutch: translated to horse power) per 10 m<sup>2</sup> of floor. In the classroom there are three 5.2 kW (1.87 kW electrical power) air conditioners. With a factor of 1.36 pk/kWel makes that round 7.6 pk. The classroom is 106 m<sup>2</sup>, therefore it is a bit oversized according to the rule of thumb.

To design a system, an accurate load profile is essential. Data from energy meters, temperature sensors, a user behaviour analysis and weather data were used to determine



of the cooling load. An energy meter installed in the classroom provides the electrical load needed to power the air conditioner.

The calculations of cooling load for the classroom in this study was made based on the cooling load calculations after VDI 2078 and instructions for simplified cooling load calculations for single air conditioners [5]. The cooling capacity is combination of internal heat gain and external heat gains. The gains here are losses, identified as the heat sources, which needs to be compensated by providing cooling from air conditioners. The internal gains are considered from: people (sensible and latent heat); lighting; electrical appliances (computer, projector, fans of air conditioners). While the external gains for the classroom are: transmission heat losses and ventilation heat losses (cooling and drying outdoor air).

To predict how the PV systems would perform with new AC air conditioners a new load profile was created this time with a COP of 4.0, which is a typical value for new AC air conditioners. For these values, a design day was also created. The design day load is used from Monday to Friday for annual calculations. For the new air conditioners is the daily load 30.02 kWh and for the current air conditioners 43.20 kWh.

Two size PV systems were simulated in PVsyst. The load used in the simulation is the load from the design day current air conditioners (COP 2.78) and new air conditioners (COP 4.0). Sharp photovoltaic modules manufactured in Indonesia were chosen. Choosing to use locally manufactured modules allows for higher feed in tariff under Indonesian policy. The

A cost analysis of the proposed grid-connected systems are calculated, this includes total investment, payback period and levelized costs. A typical PV grid connected system diagram is shown in Fig. 1 which is also showing algorithm (by arrows) flows of electricity energy to power the air conditioner.




Fig 1. PV grid connected system

### III. RESULTS

In Indonesia the average solar irradiation is about 4.8 kWh/m<sup>2</sup>,day [7]. The weather data needed for analysing and sizing a PV coupled air conditioning system is during the day, as cooling demand for the classroom is only at daytime and




Fig 2. Air conditioner consumption compared to temperature

results from previous study [6] suggested that the north east facing roof (azimuth 135°) had the highest annual irradiation, with a roof tilt of 35°.

solar irradiation of course as well. Therefore, the existing weather data was analysed over daytime from 5:00 to 18:00. The existing University of Surabaya weather station provides the temperature and daytime humidity at its campus. Coldest

months are January to August with below 28 °C and the hottest months are October and November with around 31 °C. Global solar radiation and temperature in Surabaya is shown in Fig 3. The daytime humidity is with 60 to 80 % in average also very high around the year. During the dry season (July to October) it is in general less humid than during the rainy season (November to June).




Fig 3. Global solar radiation and temperature in Surabaya

Referring to comfort zone in dependence of temperature and humidity [8] room temperatures in Surabaya should be in between 18 and 24 °C dependent on the humidity. The optimal relative humidity is in between 35 and 70 %. In addition, people feel higher temperatures more comfortable with a lower humidity than with a higher humidity. The further the air conditions are out of that zone the more uncomfortable it is for people. But the temperature difference between inside and outside should not exceed 6 K for health reasons [9]. With a daily average temperature of 28 to 31 °C, Surabaya's temperature is much higher than the comfort zone.

#### A. Existing Air Conditioners Power Consumption

Figure 2 shows measurement results from the existing classroom air conditioners. The power is cumulative values for the three air conditioners

The figure also shows the classroom temperature and the ambient temperature. At 05:30 air conditioner is switched on. The blurred lines in the consumption are when one of the air conditioners is cycling on and off. There is a rise in temperature of 2 °C which could be explained by the large number of students attending this class (87 students). Mid-day the air conditioner is switched off for an hour during lunch break. The air conditioner then runs continually until 20:00. The running times of the air conditioner were much longer than expected so for the purpose of this test only values from 07:30 to 17:30 were used.

#### B. PVsyst Simulations

Table 1 shows the main parameters for both the 8 kW and 12 kW grid connected PV systems, to simulate of supplying air conditioners both with COP 4.0 and COP 2.78. Sharp photovoltaic modules manufactured in Indonesia were chosen. These modules contain more than 40 % local components, so that a high feed in tariff of 0.27 USD/kWh can be assumed.

Figure 4 shows the power output for both the 8 kW and 12 kW systems in comparison to the air conditioner consumption with COP 2.78. The Figure gives a direct comparison of the two systems. The daily output for the 8 kW system is 28.28 kWh and 44.74 kWh for the 12 kW system. The consumption of the air conditioner is 43.20 kWh. For both systems grid backup power is needed in the morning and the evening. There are also times that both systems feed into the grid with 3.36 kWh for the 8 kW system and 11.96 kWh for the 12 kW system. The solar fraction shows the percentage of air conditioner power supplied by the PV system. The solar fraction values were 57% for the 8 kW system and 76% for the 12 kW system.

Table II gives a summary of the results from the simulation of the 8 kW and 12 kW systems for the air conditioners. The yearly solar fraction for the 8.0 kW system is 60% for the current COP 2,78 and 72% for the COP 4,0 respectively. For the 12 kW system the solar fraction is 75% with the old AC and 81% for the new AC.




Fig 4. Power output of PV System in comparison to air conditioning load

TABLE I  
PV SIMULATION PARAMETERS

Photovoltaic panels	12 kWp	8 kWp
PV Field Orientation	tilt 35° azimuth 135°	tilt 35° azimuth 135°
PV Manufacturer and Model	Sharp R245A6	Sharp R245A6
PV Technology	Si-poly	Si-poly
Nominal Power	245 Wp	245 Wp
Array global power Nominal (STC)	12.74 kWp	8.09 kWp
At operating conditions (50°C)	11.38 kWp	7.22 kWp
Total number of PV modules	52	33
Total area Module area	85.4 m <sup>2</sup>	54.2 m <sup>2</sup>
Manufacturer and Model	StecaGrid 3010	StecaGrid 2300
Operating Voltage	125-500 V	125-500 V
Nb. of inverters	4 units	3 units
Unit Nominal Power	3 kWac	2.30 kWac
Total Nominal Power	12 kWac	6.9 kWac
System Production Produced Energy	17.59 MWh/year	11.12 MWh/year
Performance Ratio PR	81.50 %	81.20 %

#### A. Financial Analysis

A cost analysis of the proposed systems was calculated, including total investment, payback period and levelized costs. Results for the 8 kW and 12 kW PV systems are given for both the current air conditioners with a COP of 2.78 and the new proposed air conditioners with a COP of 4.0. In May 2015, Indonesian's inflation rate was 6.79 %. The inflation rate forecast for 2020, 2030 and 2050 is projected to be 7.63, 7.54 and 7.56 % respectively [10], hence 7.5% was assumed in this calculation.

TABLE II  
PV SIMULATION RESULTS

COP	System	Inverter output [kWh]	Grid backup [kWh]	Feed in [kWh]	Load [kWh] Design day
2.78	8.0 kW	28.28	18.30	3.36	43.20
	12.7 kW	44.74	10.40	11.96	43.20
4.0	8.0 kW	28.28	8.00	6.25	30.02
	12.7 kW	44.74	5.22	19.93	30.02

Calculation shows that a total initial investment of 132.11m IDR (million Indonesian Rupiah) for the 8 kW system and 211.43m IDR for the 12 kW system is required. The component includes module costs and mounting, inverter costs, installation and shipping, total project costs. Margin for engineering and profit, and total investment (without 20 % TAX). VAT has not been included because the University can deduct the tax. The specific PV price for polycrystalline modules from South East Asia is currently 0.48 €/Wp [11].

With an exchange rate of 14400 IDR per Euro (25.05.2015) is the specific PV price than 6900 IDR/Wp.

The electricity price of the state owned grid operator in Indonesia is about 1500 IDR/kWh. By using modules manufactured in Indonesia, it entitles the university to get the high feed in tariff, which is assumed to 3600 IDR/kWh. This high feed in tariff makes Indonesia unique where the feed in tariff is more than double the price of electricity. This is an effort by the government to encourage the installation of grid connected PV. Even though it would make economic sense to put all produced electricity into the grid, for the purpose of this project priority will be given to powering the air conditioner first. Without any assistance from PV, the electric bill would be 17.00 m IDR. By using a PV system, the money made from the feed in tariff would mean the university would get paid instead of having to an electric bill. Using the 8 kW system the university would receive 8.75 m IDR for the first year. This would be 28.42 m IDR for the 12 kW system.. The money earned with a PV system will be constant over the years as the feed in tariff stays also constant. With increasing electricity costs the profit with a PV system decreases each year. The consumption of the new air conditioners (COP 4,0) is lower than the current ones, this gives a lower electric bill and a higher feed into the grid. For the 8 kW and 12 kW systems, 16.20 m IDR and 37.99 m IDR respectively, can be made for the first year.

The payback period is a calculation of how long it takes to recoup the investment of the project. After this time the project will become profitable. Payback periods for the different systems are shown in Table 3.

Without having a PV system, the average yearly electricity costs for powering the current air conditioners would be 43.00 m IDR. A PV system lowers these costs greatly. With the 12 kW system, the annual electricity costs would come down to 10.60 m IDR in average. If excess energy is sold to the grid operator these costs go down again to minus 22.01 m IDR. New, more efficient air conditioners reduce the energy used and with it the electricity costs to even lower cost.

TABLE III  
PAYBACK PERIOD IN YEARS WITH 7 % INFLATION RATE

System		Payback period	
		with Feed in tariff	without Feed in tariff
8 kW	COP 2.78	5.0 years	10.0 years
	COP 4.0	4.8 years	11.0 years
12.7 kW	COP 2.78	4.7 years	11.9 years
	COP 4.0	4.3 years	14.0 years

#### IV. DISCUSSIONS

The classroom was the site the PV system should be designed for. An analysis of the classroom air conditioner consumption, internal and ambient temperatures were recorded and analyzed. Based on the test results from the



home office system two different size systems were proposed and simulated using PV syst.

The co-efficient of performance (COP) of the old air conditioners is 2.7 and the suggested new air conditioners have a COP of 4. Changing to the new air conditioners has a significant impact on the solar fraction used of the PV systems. The 8.0 kW system increased from 60 % to 72 % and the 12.0 kW increased from 75 % to 81 %. The feed in values are also high this can be explained by the weekend numbers. Assuming there is no school or work during the weekend the produced electricity is fed into the grid..

Considering a project lifetime of 25 years the results are very encouraging with a payback period of 5 years or under for all systems with Feed in tariff. The payback period is quite similar for all systems, because the 12 kW system produces much more electricity but the project costs are also much higher, while the 8 kW system produces less electricity, the project costs are also lower. Once the payback period is completed the 12 kW system would become more profitable. A calculation without any feed in tariff shows a payback period of 10 to 14 years. The feed in tariff is not necessary for this project to be profitable. Many countries have lower feed in tariffs than Indonesia but a similar project could be successful there also. In all calculations without feed in tariff, excess energy is not considered. This excess energy is fed into the grid for free or could be used within the University to lower the electricity use. If this excess energy could be used the payback period would decrease. The majority of the excess electricity produced is during the weekend because the classroom is not in use. For this electricity to be useful further study would have to be done to investigate how much electricity is used during weekends in the university.

The levelized cost of energy (LCOE) represents a per-kilowatt value of electricity used over the project lifetime (25 years). Using the feed in tariff, the 12 kW PV system and the new AC units the LCOE is -3,334 IDR/kWh. This is a very profitable system and a good result for the project. Even the worst case scenario 8 kW PV, current AC and no feed in tariff has a LCOE of 1,981 IDR/kWh, which is more than half that of without PV (3,795 IDR/kWh). The projects profitability is dependent on the level of initial investment made. If the University is willing to invest in the 12 kW PV system and new air conditioning units the levelized cost of energy will be lower. However, if there is no possible feed in tariff the project size will reach a limit. The levelized cost for the 12 kW PV system using new COP 4,0 air conditioners is higher than the 8 kW system. This means the 12 kW system is oversized and the 8 kW system should be chosen.

The next step for the project would be to bid for a feed in tariff with the proposed 12.0 kW system. If the bid is unsuccessful then the 8 kW system should be installed. These changes are all very good but in reality the cost of initial investment usually has a big influence on the project. With a total investment of 132.11m IDR for the 8 kW system and 211.43m IDR for the 12 kW system a budget for the project must also be decided before continuing.

One way to reduce the cooling load of the room is to get new air conditioners with a higher COP and a lower electrical consumption. Another way to reduce the cooling load is to look at the culture of air conditioner use and thermal comfort levels. Many studies have been conducted analysing thermal comfort levels and the potential for energy reduction with regard to air conditioning. While this type of study was not possible during this work, personal observations showed that energy conservation for air conditioning was not an issue. In many places like schools, shops, cinemas and restaurants air conditioners are sometimes set very low at 17°C to 19 °C with people wearing sweaters and jackets because it's too cold. Reference [12] showed that there is no loss in thermal comfort with a 2 °C increase (from 25 °C to 27 °C) as long as a higher air flow rate was present. Reference [13] found that 34.4% reduction in energy use in buildings is possible by increasing the set temperature by 2 °C based on buildings in Taiwan. For Indonesia to become more energy efficient these concepts and mentality must be taken into consideration.

## V. CONCLUSIONS

The study showed that the collaboration between photovoltaics and air conditioning for a classroom is evident with an average of 94 % of PV electricity produced during the class hours of 07:30 to 17:30. The best way to connect PVs and air conditioning is through a grid connected system. With an average solar irradiation of about 4.8 kWh/m<sup>2</sup>/day together with a high feed in tariff, Indonesia is an attractive prospect for solar energy. Simulations showed getting a higher solar fraction than 80 % for the air conditioners will produce a high amount of excess electricity. Surabaya represents a tropical climate, that means the presented system solutions can be adopted to other cities and countries with similar weather.

## REFERENCES


- [1] K. F. Fong, C. K. Lee, and T. T. Chow, "Comparative study of solar cooling systems with building-integrated solar collectors for use in sub-tropical regions like Hong Kong," *Appl. Energy*, vol. 90, no. 1, pp. 189–195, Feb. 2012.
- [2] I. Daut, M. Adzrie, M. Irwanto, P. Ibrahim, and M. Fitra, "Solar Powered Air Conditioning System," *Energy Procedia*, vol. 36, pp. 444–453, 2013.
- [3] T. Tsoutsos, E. Aloumpi, Z. Gkouskos, and M. Karagiorgas, "Design of a solar absorption cooling system in a Greek hospital," *Energy Build.*, vol. 42, no. 2, pp. 265–272, Feb. 2010.
- [4] F. J. Aguilar, P. V. Quiles, and S. Aledo, "Operation and Energy Efficiency of a Hybrid Air Conditioner Simultaneously Connected to the Grid and to Photovoltaic Panels," *Energy Procedia*, vol. 48, pp. 768–777, 2014.
- [5] "Zeitschriftenartikel: Ueberschlaegige Bestimmung der Kuehllast. Zur Auswahl von Einzelklimageraeten – Fraunhofer IRB – baufachinformation.de." [Online]. Available: <https://www.baufachinformation.de/zeitschrift/%C3%9Cberschl%C3%A4gige-Bestimmung-der-K%C3%BChllast/2004099000346>. [Accessed: 01-Jul-2015].
- [6] "UPPSATSER.SE: Solar Energy assessment based on weather station data for direct site monitoring in Indonesia." [Online]. Available: <http://www.upsatser.se/upsats/71cb56a39e/>. [Accessed: 01-Jul-2015].
- [7] T. Guide, "Power in Indonesia," 2013.






- [8] “Grundlagen: Luftfeuchte und Gesundheit.” [Online]. Available: [http://www.cci-dialog.de/branchenticker/2013/kw05/04/grundlagen\\_luftfeuchte\\_und\\_gesundheit.html?backLink=/branchenticker/?date=31.01.2013](http://www.cci-dialog.de/branchenticker/2013/kw05/04/grundlagen_luftfeuchte_und_gesundheit.html?backLink=/branchenticker/?date=31.01.2013). [Accessed: 01-Jul-2015].
- [9] “Schaden Klimaanlagen der Gesundheit? | Apotheken Umschau.” [Online]. Available: <http://www.apotheken-umschau.de/Umwelt/Schaden-Klimaanlagen-der-Gesundheit-124241.html>. [Accessed: 01-Jul-2015].
- [10] “Indonesia Inflation Rate | 1997-2015 | Data | Chart | Calendar | Forecast.” [Online]. Available: <http://www.tradingeconomics.com/indonesia/inflation-cpi>. [Accessed: 30-Jun-2015].
- [11] “PVX spot market price index solar PV modules.”
- [12] Q. J. Kwong, N. M. Adam, and B. B. Sahari, “Thermal comfort assessment and potential for energy efficiency enhancement in modern tropical buildings: A review,” *Energy Build.*, vol. 68, pp. 547–557, Jan. 2014.
- [13] K. H. Yang and C. H. Su, “An approach to building energy savings using the PMV index,” *Build. Environ.*, vol. 32, no. 1, pp. 25–30, Jan. 1997.



# Proceedings of the 2015 International Conference on Technology, Informatics, Management, Engineering and Environment, TIME-E 2015

Country	United States - <a href="#">SJR Ranking of United States</a>	2
Subject Area and Category	<a href="#">Computer Science</a> <a href="#">Signal Processing</a>  <a href="#">Engineering</a> <a href="#">Aerospace Engineering</a> <a href="#">Electrical and Electronic Engineering</a>  <a href="#">Physics and Astronomy</a> <a href="#">Instrumentation</a>	
Publisher		
Publication type	Conferences and Proceedings	
ISSN	-	H Index
Coverage	2016	
	<a href="#">Join the conversation about this journal</a>	





journal experiences and other issues derived from the publication of papers are resolved. For topics on particular

els with your editor.

← Show this widget in your own website

Just copy the code below and paste within your html code:

```
<a href="https://www.scim
```

powered by scimagojr.com

← Show this widget in your own website

Just copy the code below and paste within your html code:








```
<a href="https://www.scim
```

powered by scimagojr.com



## Document details

[< Back to results](#) | [< Previous](#) 6 of 11 [Next >](#)






[CSV export](#)  [Download](#)  [Print](#)  [E-mail](#)  [Save to PDF](#)  [Save to list](#)  [More...](#) 

[View at Publisher](#)

Proceedings of the 2015 International Conference on Technology, Informatics, Management, Engineering and Environment, TIME-E 2015 21 January 2016, Article number 7389759, Pages 121-126

International Conference on Technology, Informatics, Management, Engineering and Environment, TIME-E 2015; Hotel Toledo InnSamosir Island, Toba Lake; Indonesia; 7 September 2015 through 9 September 2015; Category numberCFP1564U-ART; Code 119132


### Study of PV powered air conditioning for a classroom of University of Surabaya (Conference Paper)

**Tarigan, E.<sup>a,c</sup>** , **Djuwari<sup>a</sup>** , **Kartikasari, F.D.<sup>b,c</sup>** , **Fleicher, M.<sup>d</sup>** , **Howley, B.<sup>d</sup>** 

<sup>a</sup>Electrical Engineering, University of Surabaya, Jl. Raya Kalirungkut, Surabaya, 60292, Indonesia

<sup>b</sup>Informatics Engineering, University of Surabaya, Jl. Raya Kalirungkut, Surabaya, 60292, Indonesia

<sup>c</sup>Center for Renewable Energy Studies, PSET, University of Surabaya, Surabaya, 6029, Indonesia

[View additional affiliations](#) 

#### Abstract

[View references \(13\)](#)

This paper discusses the interaction between PV and air conditioning and how this can be exploited for a classroom at University of Surabaya campus. A cost analysis of the proposed grid-connected systems are calculated, including total investment, payback period and levelized costs. The most efficient way to connect PVs and air conditioning for a classroom is through a grid connected system. Simulation result shows that a 12 kWp