Paper Titles

Comparison of Commercially Pure Titanium Surface Hardness Improvement by Plasma Nitrocarburizing and Ion Implantation
p.347

Effect of Phenolic Resin and Alignment to the Quality of Prototype Composite Railway Brake Blocks
p.352

Effects of Welding Parameters in Micro Friction Stir Lap Welding of Aluminum A1100
p.356

Preparation of Uranium Nitride from Uranium Metal through by Hydriding and Nitriding Process
p.360

Simulation of Metal Flow to Investigate the Application of Antilock Brake Mechanic System in Deep Drawing Process of Cup
p.367

Effect of Equal Channel Angular Pressing and Post Heating on Microstructure and Hardness of Cu-Zn 70/30
p.373

Materials Selection in Appropriate Technology Four Focuses in Design Thinking
p.379

Study about Surface Hardening on Local Disc Brakes with Direct Current Plasma Nitrocarburizing Apparatus
p.383

The Effect of Vertical Step Block Casting to Microstructure and Mechanical Properties in Producing Thin Wall Ductile Iron
p.387

[Home](#) [Advanced Materials Research](#) [Advances in Materials, Processing and...](#) [Simulation of Metal Flow to Investigate the...](#)

Simulation of Metal Flow to Investigate the Application of Antilock Brake Mechanic System in Deep Drawing Process of Cu

Abstract:

This paper presents the importance of simulation of metal flow in deep drawing process which employs an antilock brake mechanic system. Controlling the force and friction of the blank holder is imperative to assure that the sheet metal is not locked on the blank holder and hence it flows smoothly into the die. The simulation was developed based on the material displacement, deformation and deep drawing force on flange in the radial direction, that it is controlled by blank holder with antilock brake mechanic system. The force to blank holder was applied periodically and the magnitude of force was kept constant during simulation process. In this study, the mechanical properties of the material were chosen such that they equivalent to those of low carbon steel with its thickness of 0.2 mm. The diameter and the depth of the cylindrical cup-shaped product were 40 mm and 10 mm, respectively. The simulation results showed that the application of antilock brake mechanic system improves the ability to control the material flow during the drawing process, although the maximum blank holder force of 13000 N was applied. The optimum condition was found when the drawing process was performed using blank holder force of 3500 N, deep drawing force of 7000 N, friction coefficient of 0.25 and speed of punch stroke of 0.84 mm/sec. This research demonstrated that an antilock brake mechanic system can be implemented effectively to prevent cracking in deep drawing process.

Info:

Periodical: [Advanced Materials Research](#) (Volume 789)

Main Theme: [Advances in Materials, Processing and Manufacturing](#)

Edited by: [Akhmad Herman Yuwono](#)

Pages: **367-372**

DOI: [10.4028/www.scientific.net/AMR.789.367](https://doi.org/10.4028/www.scientific.net/AMR.789.367)

Citation: **S. Candra et al., "Simulation of Metal Flow to Investigate the Application of Antilock Brake Mechanic System in Deep Drawing Process of Cup", Advanced Materials Research, Vol. 789, pp. 367-372, 2013**

Online since: **September 2013**

Authors: [Susila Candra](#), [I. Made Londen Batan](#), [Agus Sigit Pramono](#), [Bambang Pramuja](#)

Keywords: [Antilock Brake System](#), [Blank Holder Force](#), [Cracking](#), [Deep Drawing](#), [Metal Flow](#)

Export: [RIS](#), [BibTeX](#)

Price: **\$38.00**

Permissions: [Request Permissions](#)

Share: [f](#) [t](#) [p](#) [e](#) [+](#)

ADD TO CART

References

Cited by

Related Articles

Periodicals

Engineering Research

Advanced Engineering Forum

Journal of Biomimetics, Biomaterials
and Biomedical Engineering

Advances in Science and Technology

Applied Mechanics and Materials

International Journal of Engineering
Research in Africa

Foundations of Materials Science and
Engineering

Materials Science

Journal of Metastable and
Nanocrystalline Materials

Journal of Nano Research

Defect and Diffusion Forum

Solid State Phenomena

Diffusion Foundations

Materials Science Forum

Key Engineering Materials

Nano Hybrids and Composites

Advanced Materials Research

Limited Collections

Specialized Collections

Retrospective Collection

Newsletter Subscription

First Name *

Last Name *

Email *

[Home](#) [Advanced Materials Research](#) [Editor Board](#)

Advanced Materials Research

ISSN: 1662-898

[Volumes](#) [My eBooks](#) [Details](#) [Editorial Board](#)

Editor(s) in Chief

Prof. Xiao Zhi Hu

[SEND MESSAGE](#)

University of Western Australia, School of Mechanical and
Chemical Engineering; Perth, Australia, WA 6009;

Prof. Alan Kin Tak Lau

[SEND MESSAGE](#)

Swinburne University of Technology, Faculty of Science,
Engineering and Technology; John Street, Hawthorn, Australia,
VIC 3122;

Editorial Board

Dr. Peng Cao

[SEND MESSAGE](#)

University of Auckland, Department of Chemical and Materials
Engineering; Private Bag, Auckland, New Zealand, 92019;

Prof. Ionel Chicinaş

[SEND MESSAGE](#)

Technical University of Cluj-Napoca, Faculty of Materials and
Environmental Engineering, Department of Materials Science
and Engineering; 103-105 Muncii Blv., Cluj-Napoca, 400641,
Romania;

Prof. Prafulla K. Jha

[SEND MESSAGE](#)

Maharaja Sayajirao University of Baroda, Department of
Physics, Faculty of Science; Vadodara, India, 390 002;

Prof. Heinz Palkowski

[SEND MESSAGE](#)

Clausthal University of Technology, Institute of Metallurgy;
Robert-Koch-Strasse 42, Clausthal-Zellerfeld, 38678, Germany;

Wolfgang Sand

[SEND MESSAGE](#)

University of Duisburg-Essen, Biofilm Centre, Aquatic
Biotechnology; Geibelstrasse 41, Duisburg, 47057, Germany;

Dr. Ching Hua Su

[SEND MESSAGE](#)

NASA/Marshall Space Flight Center, EM31 NASA/Marshall
Space Flight Center; Huntsville, USA, 35812;

SUBSCRIBE

Subscribe to our Newsletter and get informed about new publication regularly and **special discounts for subscribers!**

GET ACCESS

SYSTEM GUIDE

DISTRIBUTORS

SUPPLEMENTS

ABOUT US

POLICY &

ETHICS

CONTACT US

IMPRINT & PRIVACY

POLICY

SITEMAP

Scientific.Net is a registered brand of Trans Tech Publications Inc.
© 2018 by Trans Tech Publications Inc. All Rights Reserved

Advances in Materials, Processing and Manufacturing

Edited by
Akhmad Herman Yuwono

TRANS TECH PUBLICATIONS

Advanced Materials Research

ISSN: 1022-6680, ISSN/ISO: Adv. Mater. Res.

Editors:

Xiao Zhi Hu, The University of Western Australia, School of Mechanical Engineering
Perth, Australia, xhu@mech.uwa.edu.au

Alan Kin Tak Lau, Hong Kong Polytechnic University, Department of Mechanical Engineering, Hung Hom, Kowloon, Hong Kong, China P.R., mmk1lau@polyu.edu.hk

Publishing Editor: **Thomas Wohlbier**, T., 105 Springdale Lane, Millersville, PA 17551, USA,
t.wohlbier@ttp.net

Editorial Board:

Barton, J., University of Southampton, School of Engineering Sciences, UK

Cao, P., University of Waikato, Department of Materials and Process Engineering, New Zealand

Chandra, T., University of Wollongong, Faculty of Engineering, Australia

Chicinas, I., Technical University of Cluj-Napoca, Department of Materials Science and Technology, Romania

Daniel, B.S.S., Indian Institute of Technology Roorkee, Department of Metallurgical and Mat. Engineering, Centre of Nanotechnology, India

Engel, U., University of Erlangen-Nuremberg, Chair of Manufacturing, Erlangen-Nuremberg, Germany

Evans, S.L., Cardiff University, Cardiff School of Engineering, UK

Gao, H., Dalian University of Technology, School of Mechanical Engineering, China P.R.

Ibbadode, A.O.A., University of Benin, Department of Production Engineering, Nigeria

Jha, P.K., Bhavnagar University, Department of Physics, India

Kim, J.K., Hong Kong University of Science and Technology, Department of Mechanical Engineering, China P.R.

Leng, J.S., Harbin Institute of Technology, Center for Composite Materials and Structures, China P.R.

Palkowski, H., Clausthal University of Technology, Institute of Metallurgy, Germany

Pullin, R., Cardiff University, Cardiff School of Engineering, UK

Sand, W., University of Duisburg-Essen, Biofilm Centre, Germany

Schikorra, M., University of Dortmund, Institute of Forming Technology and Lightweight Construction (IUL), Germany

Yin, Y.S., Shanghai Maritime University, Institute of Marine Materials Science and Engineering, China P.R.

Zhang, D.L., University of Waikato, Department of Materials and Process Engineering, New Zealand

Zhang, T.Y., Hong Kong University of Science and Technology, Department of Mechanical Eng., China P.R.

Aims and Scope:

Advanced Materials Research specializes in the very rapid publication of international conference proceedings and stand-alone volumes on topics of current interest in all areas of materials research and related topics.

Internet:

The periodical is available in full text via www.scientific.net

Subscription Information:

Irregular; approx. 150-250 volumes per year. First volume in 2013: vol. 601

The subscription rate for web access is EUR 1070.00 per year. Standing order price: EUR 108.00 per volume including online access, EUR 100.00 per volume for print only.

ISSN print 1022-6680 ISSN cd 1022-6680 ISSN web 1662-8985

Trans Tech Publications Ltd

Kreuzstr. 10 • 8635 Zurich-Durnten • Switzerland

Fax +41 (44) 922 10 33 • e-mail: ttp@ttp.net

<http://www.ttp.net>

<http://www.scientific.net>

Advances in Materials, Processing and Manufacturing

Edited by
Akhmad Herman Yuwono

Advances in Materials, Processing and Manufacturing

**Selected, peer reviewed papers from the
13th International Conference on
Quality in Research
(QiR 2013),
June 25-28, 2013, Yogyakarta, Indonesia**

Edited by

Akhmad Herman Yuwono

TTP

Copyright © 2013 Trans Tech Publications Ltd, Switzerland

All rights reserved. No part of the contents of this publication may be reproduced or transmitted in any form or by any means without the written permission of the publisher.

Trans Tech Publications Ltd
Kreuzstrasse 10
CH-8635 Dürnten-Zürich
Switzerland
<http://www.ttp.net>

Volume 789 of
Advanced Materials Research
ISSN print 1022-6680
ISSN cd 1022-6680
ISSN web 1662-8985

Full text available online at <http://www.scientific.net>

Distributed worldwide by

Trans Tech Publications Ltd
Kreuzstrasse 10
CH-8635 Dürnten-Zürich
Switzerland

Fax: +41 (44) 922 10 33
e-mail: sales@ttp.net

and in the Americas by

Trans Tech Publications Inc.
PO Box 699, May Street
Enfield, NH 03748
USA

Phone: +1 (603) 632-7377
Fax: +1 (603) 632-5611
e-mail: sales-usa@ttp.net

printed in Germany

Editorial Note

Sustainable development is a central issue in today globalization era where human being always tries to increase its quality of life from time to time. The awareness of the impact of any aspects on the environment is essential. The fulfillment of human life quality, therefore, must be always balanced with its harmony with the nature. The 13th International Conference on Quality in Research (QiR) 2013 held in Yogyakarta, Indonesia on June 25-28 2013, is aimed at bringing national and international front-liners, thinkers, academicians, executives, government and business officials, practitioners and leaders to present results of their ongoing research and to discuss a wide range of engineering, architectural and community development issues to explore innovation for enhancement of human life and environment.

In this edition of Advanced Materials Research journal, we are pleased to bring the selected collection of papers from the 13th QiR conference in the area of Materials Engineering and related topics. All of the contributing papers in this book have been peer reviewed by expert referees in order to meet professional and scientific standards. Since the conference is planned to address a wide spectrum of materials engineering, therefore, this edition is divided into the following sections: (i) Advanced and Composite Materials; (ii) Polymer and Ceramic Materials; (iii) Materials Manufacturing and Processes; (iv) Corrosion and Degradation of Materials; and (iv) Extraction of Materials.

We do realize that the success of 13th International Conference on Quality in Research (QiR) 2013 and the publication of this book are derived from the very hard work of lots of people. Therefore, we would like to thank all of the authors who have spent their time to contribute with their genuine results, and all of the reviewers for their valuable dedication, time and comments to ensure the published papers have reached the international journal standard. We also would like to take this opportunity to thank many people and organizations who have supported this conference. Finally, we hope that this book will serve as a good archive of research findings and provide useful directions for future research.

Editor-in-chief

Akhmad Herman Yuwono

Table of Contents

Editorial Note

v

Chapter 1: Advanced and Composite Materials

Atomic Layer Deposition of Inverse Opals for Solar Cell Applications S.K. Karuturi, L.J. Liu, L.T. Su, W.B. Niu and A.L.Y. Tok	3
The Influence of Various Percentage of Al_2O_3 by Using Vortex Method to Tensile Strength and the Distribution of Al_2O_{3p} Composite S. Junus, A. Zulfia, E. Tanoto and L. Mariani	8
Modifications of Multi-Walled Carbon Nanotubes on Zinc Oxide Nanostructures for Carbon Monoxide (CO) Gas Sensitive Layer M. Iqbal, B. Yulianto and N. Nugraha	12
An Investigation of Structure and Complex Impedance Behavior of Composite $(1-X)Ba_{0.5}Sr_{0.5}Fe_{11.7}Mn_{0.15}Ti_{0.15}/XLa_{0.7}Ba_{0.3}MnO_3$ V.V.R. Repi and A. Manaf	16
Electrochemical Behavior of $Li_4Ti_5O_{12}$ under <i>In Situ</i> Process of Sintering and Surface Coating with Cassava Powder B. Prihandoko, A. Subhan and S. Priyono	21
Synthesis of Highly-Ordered TiO_2 through CO_2 Supercritical Extraction for Dye-Sensitized Solar Cell Application B. Priyono, A.H. Yuwono, B. Munir, A. Rahman, A. Maulana and H. Abimanyu	28
Deformation Behaviour of Silicon Carbide Reinforced Al-7Si Composite after Ballistic Impacts B.T. Sofyan, D. Rahmalina, B. Suharno and E.S. Siradj	33
Hydrogen Absorpsivity-Desorbsivity of Mg Doped by Ni, Cu, Al Produced by Mechanical Alloying W. Widyastuti, B.P. Febrian and S. Sutarsis	37
Crystallite Growth Kinetics of $BaFe_{12}O_{19}/SrTiO_3$ Based Composites Derived from Mechanical Alloying R.D. Widodo, A. Manaf and P. Sardjono	42
Crystal Structures and Thermal Properties of Bamboo Nanofiber Reinforced-Composite Friction Materials of Glass and Metal Wastes S. Madnasri, S.S. Edi and D.S. Saputra	49
Formation and Characterization of MMCs Alloy Al-5%Cu-4%Mg/SiC(p) by Thixoforming Process Y. Afandi, A. Zulfia, D. Priadi and I.N. Jujur	56
Study on PbSn Composites Produced by Powder Metallurgy as Core Bullet Projectile W. Widyastuti, V.A. Setyowati and T. Akbar	60
Electroless Plating of Al_2O_3 Particles Reinforced Composites A. Zulfia and A.I. Adyatma	66

Characterization of Al-7Si-Mg-Cu Turbine Impeller Produced by Investment Casting	
M. Syahid, B.T. Sofyan, S.G. Basuki and B. Adam	324
Research on the Manufacturing of Steam Turbine Blade by Using Investment Casting Technology	
Hafid.....	330
Mechanical Properties and Microstructure of Welded Dissimilar Metals Using Buttering & Non-Buttering Layer	
W. Winarto, M. Anis and T.P. Hertanto	341
Comparison of Commercially Pure Titanium Surface Hardness Improvement by Plasma Nitrocarburizing and Ion Implantation	
A.S. Darmawan, W.A. Siswanto and T. Sujitno.....	347
Effect of Phenolic Resin and Alignment to the Quality of Prototype Composite Railway Brake Blocks	
A. Triono, W.P. Ign, S.S. Brodjonegoro and A. Ramelan.....	352
Effects of Welding Parameters in Micro Friction Stir Lap Welding of Aluminum A1100	
A.S. Baskoro, A.A.D. Nugroho, D. Rahayu, Suwarsono, G. Kiswanto and W. Winarto.....	356
Preparation of Uranium Nitride from Uranium Metal through by Hydriding and Nitriding Process	
H. Suwarno.....	360
Simulation of Metal Flow to Investigate the Application of Antilock Brake Mechanic System in Deep Drawing Process of Cup	
S. Candra, I.M.L. Batan, A.S. Pramono and B. Pramujati.....	367
Effect of Equal Channel Angular Pressing and Post Heating on Microstructure and Hardness of Cu-Zn 70/30	
S. Suryadi, R.A.M. Napitupulu, D. Priadi, A. Suhadi and E.S. Siradj	373
Materials Selection in Appropriate Technology Four Focuses in Design Thinking	
C.P.M. Sianipar, H. Taufiq, H.R. Estiningtyas, K. Dowaki, A. Adhiutama and G. Yudoko	379
Study about Surface Hardening on Local Disc Brakes with Direct Current Plasma Nitrocarburizing Apparatus	
U. Sudjadi	383
The Effect of Vertical Step Block Casting to Microstructure and Mechanical Properties in Producing Thin Wall Ductile Iron	
R.D. Sulamet-Ariobimo, J.W. Soedarsono and I.P. Nanda	387
Resolving Individual Solute Levels of AA6061 through Multiple Sub-Ambient Temperatures Thermoelectric Power Measurements	
D.D. Rianti and S. van der Zwaag.....	394
Effect of Rolling Direction to the Strength of a Thin-Walled Steel SHS Beam under Concentrated-Compressive Load and Bending Moment	
A.M. Kadir, D. Priadi, E.S. Siradj and H. Setiyono	398
Optimization Design of Airfoil Propellers of Modified NACA 4415 Using Computational Fluids Dynamics	
Sudarsono, Purwanto and J. Wahyuadi.....	403
Analysis of Micro-Channels Manufacturing of Acrylic Using Low Power CO₂ Laser	
A.S. Baskoro, A. Siswanta and K.G.S. Ismail	408

Simulation of Metal Flow to Investigate the Application of Antilock Brake Mechanic System in Deep Drawing Process of Cup

Susila Candra^{1,a}, I Made London Batan^{1,b}, Agus Sigit P^{1,c},
 Bambang Pramujati^{1,d}

¹Mechanical Engineering, Institute of Technology Sepuluh Nopember (ITS), Indonesia

^asusilac@yahoo.com, ^blondbatan@me.its.ac.id, ^cpramono@me.its.ac.id, ^dpramujati@me.its.ac.id

Keywords: deep drawing, metal flow, blank holder force, antilock brake system, cracking.

ABSTRACT This paper presents the importance of simulation of metal flow in deep drawing process which employs an antilock brake mechanic system. Controlling the force and friction of the blank holder is imperative to assure that the sheet metal is not locked on the blank holder, and hence it flows smoothly into the die. The simulation was developed based on the material displacement, deformation and deep drawing force on flange in the radial direction, that it is controlled by blank holder with antilock brake mechanic system. The force to blank holder was applied periodically and the magnitude of force was kept constant during simulation process. In this study, the mechanical properties of the material were chosen such that they equivalent to those of low carbon steel with its thickness of 0.2 mm. The diameter and the depth of the cylindrical cup-shaped product were 40 mm and 10 mm, respectively. The simulation results showed that the application of antilock brake mechanic system improves the ability to control the material flow during the drawing process, although the maximum blank holder force of 13000 N was applied. The optimum condition was found when the drawing process was performed using blank holder force of 3500 N, deep drawing force of 7000 N, friction coefficient of 0.25 and speed of punch stroke of 0.84 mm/sec. This research demonstrated that an antilock brake mechanic system can be implemented effectively to prevent cracking in deep drawing process.

Introduction

A drawing process refers to a sheet metal forming process where a sheet metal is radially drawn into a forming die by implementing a mechanical action of punch. It is called "deep drawing" when the depth of the drawn part exceed the diameter of the product. Although this process has been known and used for many years, there are many problems that may occur during the process and still become the attraction of many researchers. The process of deep drawing and problems that often occur in this process are illustrated in Figure 1.

Figure 1. (a) Process of drawing deep; (b) Flow of material and stress deformation; (c) Crack and wrinkle defect.

Controlling the flow of material properly during a deep drawing process is very important in order to prevent product defects such as wrinkling and cracking. Endelt, B [1] investigate the application of a flexible blank-holder system to adjust the blank-holder pressure individually in different zones in the flange area [1]. The draw-in of the flange is influenced by the blank-holder pressure and therefore, the draw-in can be controlled by adjusting/controlling the pressure. Online

drawn-in measurement can be performed using laser technology in which its sensors based on mechanical devices. However, this method requires sensors and equipment that are not applicable to the industry.

The magnitude of the blank holder force is an important factor in the forming process and hence the proper magnitude has to be determined properly. In this study, a variable blank holder force (VBHF) approach to deep drawing is employed [2][5][6]. This study provides information about the optimal gap to prevent wrinkling of the material, which will be used as data in this simulation. It was found that the optimal gap is no more than 117% the thickness of the material [2].

Gavas, M., studied the use of a simple mechanical antilock brake system (ABS) to control the material flow in deep drawing process [3][4]. The experiment proved that the additional mechanism helps to ease the flow of the material into the die yield to the possibility of deeper drawing process. However, the importance stage prior to experimental process, i.e. simulation, was not performed. Therefore, investigating various materials having different material properties as well as dimensions would be very difficult and expensive. It is due to different arrangement of system and most likely different equipment are needed in order to perform such different experiment set-up and test.

Based on the description above, it is clear that the control of blank holder force is an important parameter that must be considered. Therefore this paper will discuss about the application blank holder with anti lock brake system, in order to further optimize the flow of material towards the radial (not locked) and tangential (not too fast). The results of this study present the material flow simulations using a blank holder with antilock brake system, as has been done by M Gavvas [4]. Validation of the method by comparing the simulation results with Gavvas's experiment, related to the condition of material flow and material formability.

System Equation

Simulation model of anti-lock system in the process of deep drawing requires the development of material flow equations between the surface of the die and blank holder, the function of blank holder force and the condition of the process. The free body diagram (FGD) of deep drawing process and product dimensions are illustrated in Figure 2a and 2b, respectively.

Figure 2.a. FGD of deep drawing on cylindrical products, b. Product dimensions

Based on FGD 1 in Figure 2.a. the equation of blank holder force can be determined as follows:

$$F_{bh} = M_1\ddot{y}_1 + B_1\dot{y}_1 + K_1y_1 \quad (1)$$

F_{rh} represents the force that controls the flow of metal into the die. The magnitude of restraining force (F_2) can be drawn from the equilibrium of force in flange as shown in FGD II of Figure 2.a.

$$F_2 = M_2 \ddot{x}_2 + 2\mu(M_1 \dot{y}_1 + B_1 \dot{y}_1 + Ky_1 + M \dot{g}) + B_2 \dot{x}_2 + A \quad (2)$$

Here, the variable "A" is the ideal stress deformation (deformation factor), which is obtained from the following equation:

$$A = \pi \cdot D_m \cdot s_0 \cdot e^{\mu \pi / 2} \{1.15 \sigma_0 (\frac{x_2}{r_m})\} \quad (3)$$

where, σ_0 is the material yield stress, D_0 is the initial blank diameter, D_m is the mean diameter, s_0 is the thickness of material; μ is the coefficient of friction and x_2 is the position of material flows for a moment after pressure is applied.

Deep drawing force is the sum of tensile force on the flange and bending force on die radius, and therefore, the equation of deep drawing force is:

$$F_d = M_2 \ddot{x}_2 + 2\mu(M_1 \dot{y}_1 + B_1 \dot{y}_1 + Ky_1 + M \dot{g}) + 2B_2 \dot{x}_2 + \pi \cdot D_m \cdot s_0 \cdot e^{\mu \pi / 2} \{1.15 \sigma_0 (\frac{x_2}{r_m})\} + \pi \cdot D_m \cdot s_0 \cdot \{ \frac{\sigma_0 s_0}{2r_D} \} \quad (4)$$

Having $\sigma_0 = 309 \text{ N/m}^2$, $D_0 = 56.7 \text{ mm}$; $r_0 = 28.35$, $D_p = 40 \text{ mm}$; $s_0 = 0.2 \text{ mm}$; $D_m = D_p + s_0 = 40.2 \text{ mm}$; $r_D = \text{die radius} = 1 \text{ mm}$, substituting equation (1) into (4), the movement of flange modeling yields:

$$\ddot{x}_2 = \frac{1}{M_2} \{F_d - 2\mu(M_1 \dot{y}_1 + B_1 \dot{y}_1 + Ky_1 + M \dot{g}) - 2B_2 \dot{x}_2 - 446.32 e^{1.57\mu} (x_2) - 780.07\} \quad (5)$$

Equation (5) is used as a mathematical model of the simulation system for the application of blank holder by using antilock braking mechanic system.

The flow of material on the surface of the flange and into the die follows the rule of constant volume, and the following relationship can be obtained:

$$x_{2d} = \frac{1}{0.8} x_2 \text{ and } V_{2d} = \frac{1}{0.8} V_2 \quad (6)$$

and then,

$$y_{3d} = 0.8 x_{2d} \text{ and } V_{3d} = 0.8 V_{2d} \quad (7)$$

Deep Drawing Equipment With Antilock Brake System Application [3][4]

The design and the development of deep drawing with the anti lock brake mechanic system is shown in Figure 3 [3][4].

Figure 3 Scheme of deep drawing machine using application of blank holder with anti lock brake system [3][4]

If the path of shaft in the radial direction of eccentric was approached with a sinusoidal equation, therefore eccentricity Z can be described as an amplitude. While setting the distance gap represents a shift graphic of sinusoidal up and down, therefore the sinusoidal trajectory of eccentric axis would represent the mechanism of anti lock braking/hammering mechanic system. And with these mechanisms system, the deep drawing force (F_d) can be modelled independently. As well as the simulation modelling would describe the influence of blank holder Force (F_{bh}) against the movement of flange and the metal forming. Then, refers to the equation (5) above and the mechanism of anti lock brake system, furthermore the algorithm programming/ simulation block diagram is created.

Block and Computer Simulation

A block diagram for dynamic simulation of the mechanism of anti-lock brake system can be formed using equations 4 and 5, and the results are illustrated in Figure 4.a. The model parameters used for simulation are given below.

Material of blank sheet: low carbon steel sheet;	μ = coefficient of friction = 0.25 (palm oil)
Gap = ± 5 mm following reference [1] and [2];	x_2 = The position of flange
$M_2 = 1$ N (weight of blank sheet);	$M_1 = 500$ N (weight of blank holder plate)
$B_1 = 600$ Ns/mm (value of damping coefficient);	$B_2 = 100$ Ns/mm (value of damping coefficient on flange surface)
$K_1 = 1000$ N/mm (value of spring coefficient);	$F_{bh} = 3500$ N; $F_d = 7000$ N (average of Deep Drawing Force)
$\sigma_0 = 309$ N/mm ² ;	$D_0 = 56.7$ mm; $r_0 = 28.35$; $D_m = 40.2$ mm
$s_0 = 0.2$ mm; $r_D = \text{die radius} = 1$ mm;	$D_p = 40$ mm

Figures 4.b and 4.c show the simulation result of deep drawing process, i.e. the blank holder displacement and velocity, respectively. It can be seen that both displacement and velocity of blank holder when the drawing process is performed using anti lock brake system are lower than it is performed without anti lock mechanism. It is due to the fact that the application of anti lock mechanism allows the metal to flow more freely since the magnitude of displacement and velocity are influenced by the applied force on the blank holder.

Figure 4.a. Block diagram of simulation the material flow by using the antilock brake systems, b and c. Displacement y_1 and velocity V_1 .

Results and Discussions

Figure 5 illustrate the simulation of the drawn material which it flows is not obstructed when the antilock braking system is used in the system. The results show that the material displacement (x_2) on the flange reach approximately 6.9 mm and the speed of punch stroke of 0.84 mm/sec. It can be observed that the displacement of the flange can only reach less than 6.4 mm when the antilock braking system is not employed. Increasing in flange displacement lead to increasing in material formability, and in this case, the formability increases by 30%. Similar results were indicated by Gavas's experiment [3][4]. He also proved that the applications of antilock braking system blank holder yields increases of material formability.

Figure 5. a. The Graphic of velocity (on Blank Holder) V_2 with and without antilock; b. Displacement graphic of sheet material in the flange (x_2)

Figure 6 shows that although the applied holder force reaches its highest magnitude of 13000 N, the antilock braking system still quite effective to avoid locking in the material flow. It means that the system is capable of controlling flow of material under a very high holding force. In order to optimize the application blank holder on this system, and to improve the ability to avoid locking in the flow of materials, the gap between the upper dead point and lower dead points (see Figure 3) shall be adjusted properly. All the simulations results above agree with the experiment of application anti-lock brake system that was performed by Gavas [3][4], and hence his method can be considered feasible for production.

Figure 6. The Displacement of material in the flange (x_2) with the magnitude of F_{bh} 13000 N.

Summary

The application blank holder with antilock brake systems to control the material flow is one of the alternative methods to prevent sheet material to wrinkle and/or crack. The simulation results showed that these system capable of controlling the flow of material smoothly even though the

value of blank holder force reaches the maximum value of 13000 N. It was suggested that the optimum value of blank holder force is set approximately 3500 N, deep drawing force of 7000 N, friction coefficient of 0.25 and speed of punch stroke of 0.84 mm/sec. The anti-lock brake system would increase the material formability up to 30%. An open loop brake mechanics system has been implemented, however several drawbacks were noticed. The simulation results also showed that a closed loop system can be employed to improve the performance of the implemented open loop brake mechanics system.

References

- [1] Benny Endelt, Soren Tommerup, Joachim Danckert, A novel feedback control system-Controlling the material flow in deep drawing using distributed blank-holder force, *Journal of Materials Processing Technology*, 2013.
- [2] Satoshi Kitayama, Satoshi Hamano, Koetsu Yamazaki, Tatsuo Kubo, Hikaru Nishikawa and Hiroshi Kinoshita A closed-loop type algorithm for determination of variable blank holder force trajectory and its application to square cup deep drawing, *Journal of Adv. Manufacturing Technology* 2010.
- [3] M. Gavas, "Deep drawing with anti-lock braking system (ABS)", *Journal Mechanism and Machine Theory* 41, 2006.
- [4] Muammer Gavas, "Increasing the drawing height of conical square cups using anti-lock braking system (ABS)", *Journal of Mechanical Science and Technology* 23 page3079~3087, 2009.
- [5] Susila Candra, I Made Londen Batan, Experimental Study and Analysis of the Influence of Drawbead against Restriction and Deep Drawing Force of Rectangular Cup-Cans with Tin Plate Material, 3rd International Conference on Mechanical and Manufacturing Engineering 2012, (ICME2012) UTHM Malaysia, and published online, in *Journal of Applied Mechanics and Materials* Vol.315 pp 246-251, Trans Tech Publications, Switzerland, doi:10.4028/www.scientific.net/AMM.315.246, 2013.
- [6] Susila Candra, Dedi Priadi, Henky S Nugroho, Analysis of The Influence of Drawbead and Parameters Process on The Establishment of Rectangular-Can with The Material T4 CA-B Tin Plate, Thesis Master Degree, Mechanical Engineering, University of Indonesia, 2002.
- [7] Kurt Lange : "*Hand Book Of Metal Forming*", Mc Graw Hill Co. 1985.

Figure description: (Left) SEM image of ZnO nanorod on ITO substrate for dye sensitized solar cell application;
(Right) TE image of mesoporous silica for drug delivery application

9 783037 857571

ISBN-13: 978-3-03785-757-1

Advanced Materials Research Vol. 789

Electronically available at <http://www.scientific.net>